



Great Lakes Case & Cabinet Co., Inc.
P.O. Box 551
Edinboro, PA 16412
Phone: 814.734.7303
Fax: 814.734.3907

Customer Name _____	Phone _____	E-mail _____
Quantity Required _____	Target Price _____	Project Timeline _____
First Unit Required by Date _____	Comparable Competitive Unit Brand/Model # _____	

ELECTRICAL CONFIGURATION

Power Input			
Quantity**	Plug Type	Input AMPS	Input VOLTS
	5-15P	15	125
	L5-15P	15	125
	5-20P	20	125
	L5-20P	20	125
	6-20P	20	250
	L6-20P	20	250
	L14-20P	20	125/250
	L21-20P	20 x 3~	120/208 WYE
	L5-30P	30	125
	L6-30P	30	250
	L14-30P	30	125/250
	L15-30P	30 x 3~	250 Delta
	L21-30P	30 x 3~	120/208 WYE
	IEC C-20 Inlet (No Cord)	20/16*	125 or 250
	IEC Pin & Sleeve 2 Pole / 3 Wire	20/16*	250/230*
	IEC Pin & Sleeve 3 Pole / 4 Wire	20	250 3~
	IEC Pin & Sleeve 2 Pole / 3 Wire	30/32*	250/230*
	IEC Pin & Sleeve 3 Pole / 4 Wire	30	250 3~
	IEC Pin & Sleeve 2 Pole / 3 Wire	60/63*	250/230*
	IEC Pin & Sleeve 3 Pole / 4 Wire	60	250 3~
	Cord Length		

Power Output		
Quantity	Receptacle Type	AMPS VOLTS
	5-15R Duplex	15 125
	5-15R Individual	15 125
	L5-15R Duplex	15 125
	5-20R Duplex	20 125
	5-20R Individual	20 125
	L5-20R	20 125
	6-20R Duplex	20 250
	L6-20R	20 250
	L5-30R	30 125
	L6-30R	30 250
	IEC C-13	15/10* 125 or 250
	IEC C-19	20/16* 125 or 250
	Other - Please Specify	

PHYSICAL CONFIGURATION




Dimensional Limits		Mounting Orientation
Length		Horizontal
Width		Vertical
Height		
HARDWIRED OPTIONS		
Quantity**		
	6" Wire Tails with removable plate	
	Flexible Conduit	
	Terminal Block	

*Rating for CE products
**Quantity = # of circuits

Power Switch		Surge Supression
	No	No
	Yes	Yes
	Yes - With Cover	
Local Current Monitoring		Remote Current Monitoring
	No	No
	Yes - Current (Amps) Only	Yes, Circuit Level
	Yes - Scrolling Display (Volts, Amps, Watts, Power Factor)	Yes, Outlet Level
Circuit Breakers		Isolated Ground
	No (Required by NEC in some units)	No
	Yes	Yes
Environmental Monitoring		Remote Switching
	No	No
	Yes	Yes

ADDITIONAL INFORMATION

AMP		NEMA STRAIGHT-BLADE PLUG		NEMA STRAIGHT-BLADE OUTLET	
15	125	5-15P		5-15R	
20	125	5-20P		5-20R	
20	250	6-20P		6-20R	
AMP		NEMA TWIST-LOCK PLUG		NEMA TWIST-LOCK OUTLET	
15	125	L5-15P		L5-15R	
20	125	L5-20P		L5-20R	
30	125	L5-30P		L5-30R	
20	250	L6-20P		L6-20R	
30	250	L6-30P		L6-30R	
20	250	L14-20P		L14-20R	
30	250	L14-30P		L14-30R	
20	120/208	L21-20P		L21-20R	
30	120/208	L21-30P		L21-30R	
30	250 3~	L15-30P		L15-30R	
50	250	3P, 4W CALIF. STYLE		3P, 4W CALIF. STYLE	

AMP	VOLT	IEC POWER INLET	IEC POWER OUTLET
15/10*	125 or 250	C-14 	C-13 
20/16*	125 or 250	C-20 	C-19 

AMP	VOLT	PIN & SLEEVE			
20/16*	250/230*	2P, 3W		2P, 3W	
20	250	3P, 4W		3P, 4W	
30/32*	250/230*	2P, 3W		2P, 3W	
30	250	3P, 4W		3P, 4W	
60/63*	250/230*	2P, 3W		2P, 3W	
60	250	3P, 4W		3P, 4W	

* Rating for CE products